

BTX05120D

1200V Silicon Carbide Diode

Features

- 1200-Volt Schottky Rectifier
- Shorter recovery time
- High-speed switching possible
- High-Frequency Operation
- Temperature-Independent Switching Behavior
- Extremely Fast Switching
- Positive Temperature Coefficient on VF


Benefits

- Higher safety margin against overvoltage
- Improved efficiency all load conditions
- Increased efficiency compared to Silicon Diode alternatives
- Reduction of Heat Sink Requirements
- Parallel Devices Without Thermal Runaway
- Essentially No Switching Losses

Applications

- Switch Mode Power Supplies
- Power Factor Correction
- Motor Drives
- HID Lighting

Package



Absolute Maximum Ratings

T_C = 25° C unless otherwise noted

Symbol	Parameter	BTX05120D	Units
VRRM	Repetitive Peak Reverse Voltage	1200	V
VRSM	Surge Peak Reverse Voltage	1200	V
VDC	DC Blocking Voltage	1200	V
IF	Continuous Forward Current @T _c =25°C @T _c =135°C @T _c =150°C	20.4 10.5 5	A
IFRM	Repetitive Peak Forward Surge Current @T _C =25°C, tp = 10 ms, Half Sine Wave	25	A
IFSM	Non-Repetitive Peak Forward Surge Current @T _C =25°C, tp = 10 ms, Half Sine Wave	43	A
IF-MAX	Non-Repetitive Peak Forward Surge Current @T _C =25°C, tp = 10 us, Plus	370	A
Ptot	Power Dissipation @T _c =25°C @T _c =110°C	163 70	W
T _J , T _{stg}	Operating Junction and Storage Temperature	-55 to +175	°C

Electrical Characteristics

$T_C = 25^\circ C$ unless otherwise noted

Symbol	Test Conditions	Test Conditions	Min	Typ	Max	Unit
VF	Forward Voltage	IF=5A, $T_C=25^\circ C$ IF=5A, $T_C=175^\circ C$	-	1.5 2.3	1.8 3.0	V
IR	Reverse Current	$VR=1200V, T_C=25^\circ C$ $VR=1200V, T_C=175^\circ C$	-	2 50	20 100	μA
QC	Total Capacitive Charge	$VR = 600V, IF = 5A$ $T_J = 25^\circ C$ $Qc = \int_0^{V_r} C(V) dv$	-	24	-	nC
C	Total Capacitance	$VR = 0V, T_J = 25^\circ C, f = 1MHz$ $VR = 400V, T_J = 25^\circ C, f = 1MHz$ $VR = 800V, T_J = 25^\circ C, f = 1MHz$	-	340 22 18	-	pF
EC	Capacitance Stored Energy	$VR=800V$	-	12	-	μJ

Thermal Characteristics

Symbol	Parameter	Typ	Unit
R _{θJC}	Thermal Resistance from Junction to Case	0.92	°C/W

Typical Characteristics




Figure 1. Forward Characteristics




Figure 2. Reverse Characteristics

Typical Characteristics




Figure 3. Capacitance vs. Reverse Voltage




Figure 4. Total Capacitance Charge vs. Reverse Voltage




Figure 5. Capacitance Stored Energy




Figure 6. Power Derating




Figure 7. Current Derating





Figure 8. Transient Thermal Impedance

Mechanical Dimensions for TO-252



DIMENSIONS IN MILLIMETERS		
SYMBOL	MIN	MAX
A	2.18	2.4
A1	—	0.2
A2	0.9	1.17
b	0.65	0.9
b3	4.95	5.5
c	0.43	0.89
D	5.97	6.22
D1	5.21	—
E	6.35	6.8
E1	4.32	—
e	2.286BSC	
H	9.4	10.5
L	0.38	1.78
L1	2.90BSC	
L2	0.51BSC	
L3	0.88	1.28
L4	—	1.02
L5	1.65	1.95
θ	0°	10°